

# ONKYO®

## ONKYO TX-RZ740-B

243984

SRP 949,00 €

**949,00 €**



A higher standard of sound

Kleur



Stijl

**STANDARD, UK VERSION**

### PRODUCT DETAILS

#### TX-RZ740 9.2-Channel Network A/V Receiver

The TX-RZ740 not only elevates sound, but also that satisfied feeling you get every time you switch it on. The extra weight of the custom transformer, custom 10,000 F capacitors and aluminium heat-sink speak of an amp built for high-current power, enabling 3D audio to exhibit true-to-life spatiality and pin-point localization. Bass force is terrific, dynamics blindingly fast and resolution grainless. Next-Generation Network Audio gathers multi-room platforms supported by 802.11ac Wi-Fi, or enjoy powered and unpowered audio distribution. The receiver, which supports up to 7.2.4-ch of 3D sound with external amp, is certified for IMAX Enhanced and is THX Certified Select for a cinema-reference experience. From how it sounds to the way, it makes you feel, the TX-RZ740 is made to savor now and in the future.

#### Product Highlights

- 185 W/Ch THX Certified Select RZ Series DAA system
- Works with Sonos, Chromecast built-in, AirPlay 2, DTS Play-Fi, FlareConnect, Spotify, Amazon Music, TIDAL, Deezer, TuneIn
- Supports 5.2.4-ch Dolby Atmos and DTS:X playback
- 11.2-ch pre-outs and processing for 7.2.4 layouts
- Dolby Atmos Height Virtualizer
- IMAX Enhanced certified for IMAX digital remasters
- Refined HDMI grounds, SoC board, and power amps
- HDMI Sub/Zone 2 output for a sub-display or projector
- Quad-core SoC supports 802.11ac (2x2 MIMO) Wi-Fi
- Zone 2 and Zone 3 speaker outputs
- Zone 2 and Zone 3 DACs for D/A audio in three rooms
- Zone 2/Zone B and Zone 3 line-outs share D/A audio
- Stereo Assign Mode supports Height-channel playback
- DSP-based Vocal Enhancer improves dialog audibility
- OSD features media input/output data display function
- HDMI supports 4K/60p, 4K HDR, BT.2020, HDCP 2.2
- AccuEQ Advance 9-point calibration with AccuReflex
- Volume memory-presets for A/V inputs via front panel

- IP control, RS-232C, 12 V trigger output and IR input

Amplifier Features

- 185 W/Ch (6 , 1 kHz, 10% THD, 1 channel driven), 175 W/Ch (6 , 1 kHz, 1% THD, 1 channel driven, IEC)
- Certified for IMAX Enhanced and THX Certified Select
- Dynamic Audio Amplification with RZ Series Build
- Ultra-wide 5 Hz-100 kHz frequency response
- Custom-Built High-Current Low-Noise Power Transformer
- Custom high-current smoothing capacitors
- Non-phase-shift amp topology with discrete output stage
- Thick resonance-controlled extruded aluminium heat-sink
- Strengthened power-supply line for high-current dynamics
- Refined HDMI grounds and short signal-paths reduce noise
- Isolated SoC board reduces interference
- High current capability for 4-ohm speaker drive
- AKM (AK4458) 384 kHz/32-bit multichannel D/A conversion
- VLSC (Vector Linear Shaping Circuitry) noise filtering (Front L/R)
- PLL (Phase Locked Loop) anti-jitter technology for SPDIF audio
- Direct and Pure Audio modes for source-authentic expression
- Independent tone controls (bass/treble) for all channels (Zone 3 excluded)

## Specificaties

### Product attributen

EAN:	4573211154689
Fabrieksnummer:	TX-RZ740(B)MMP
Productgewicht:	12.15 kilograms